

Digital Rotational Viscometer



SALIENT FEATURES:

- Auto Range function
- More number of speed options
- Direct Viscosity reading and temperature display
- Large bright back-light LCD Display
- Viscosity value is accurate to 0.1 mpa.s
- With automatic scanning function, the instrument can automatically recommend a suitable combination of rotor and speed
- Can automatically display the range of viscosity that can be measured by the selected combination

SPECIFICATIONS:

Model	GV-100	GV-200
Make	Galaxy	Galaxy
Measuring Range mpa.s	20~20,00,000 mpa.s	20~60,00,000 mpa.s
Measurement Resolution	0.1 mpa.s (Full scale)	0.1 mpa.s (Full scale)
Speed	0.3, to 100 RPM	0.1 to 200 RPM
No of Speed	18 speed settings	58 speed settings
No of Standard Spindle	4	
Display	LCD	
Auto Scan Function	Can automatically scan and recommend the preferred combination of rotor and speed	
Temperature Monitoring	Optional - Feature available	
Measurement Accuracy	±1% F.S	
Repeatability	± 0.5% F.S	
Output	RS 232C Interface	
Power Supply	AC 220V / 50Hz	
Dimension	300 × 300 × 450 mm	
Weight	9 kgs	

STANDARD

ACCESSORIES:

- 4 spindles
- Spindle Guard Leg
- Power Cord
- Stand Set
- Instruction Manual