

Turbidity Meter

with TSS measuring mode



MODEL: TB-200

Turbidity is the cloudiness or haziness of a fluid caused by large numbers of individual particles that may or may not invisible to the naked eye.

SALIENT FEATURES:

- 2 to 7 points calibration using the Formazin Standards
- Selectable 4 turbidity units - NTU, FNU, EBC and ASBC
- TSS conversion factor ensures the accurate measurement of the total suspended solids.
- Auto-Read function senses and locks a stable reading
- Setup menu allows setting the date and time, measurement mode, resolution etc
- Password protection prevents the unauthorized calibration and settings

SPECIFICATIONS:

Model	TB-200
Make	Galaxy
Turbidity Range	0~2000 NTU, 0~ 500 EBC, 0~ 9999 ASBC
Turbidity Resolution	0.01 (0~99NTU), 0.1(100~999NTU), 1(1000~2000NTU)
Turbidity Accuracy	±2% of reading (0~500NTU), ±3% of reading (501~2000NTU)
Calibration Points	2 to 7 points
Calibration Standards	0.02, 10, 200, 500, 1000, 1500, 2000 NTU
TSS Range	Depending on the TSS conversion factor
TSS Accuracy	3% of reading
Light Source	Infrared-emitting diode (850nm)
Detector	Silicon Photodiode
Stray Light	< 0.02 NTU
Sample Vial	60(H) x 25(dia) mm
Memory & Data Output	200 data sets & USB Data output
Operating Temperature	0~50°C
Display	4.5 inches TFT LCD
Power Supply	DC12V Power Adapter
Dimensions & Weight	250 x 177 x 96 mm & 1.2 kg

STANDARD

- Adapter
- Instruction Manual

ACCESSORIES:

- Sample Vial

- Standard Solution