

Refrigerated Circulating Bath



SALIENT FEATURES:

- PT-100 temperature sensor for accurate results
- Both side handle for easy moving
- Overheat protection and liquid level alarm function
- Fast cooling, low noise, low vibration
- Stable & reliable performance
- Microprocessor based PID controlled results in high precision
- Programable temperature controller
- Liquid to be used: 5°C & below: Alcohol or Anti-freeze
5 ~ 85°C : Pure water
85 ~ 95°C : 15% Glycerin & water

SPECIFICATIONS:

Model	RCB-6	RCB-12
Make	Galaxy	Galaxy
Temp. Control Range	-20°C ~ 100°C	
T Resolution & Accuracy	Resolution: 0.01°C, Accuracy: ±0.05°C	
Temp. Control	Microprocessor PID	
Display	LCD	
Refrigeration Mode	Air cooled refrigeration through compressor	
Refrigerant	R134A	
Pump Circulation	Internal & External	
Temp. Sensor	PT-100	
Pump Flow Rate	6L/min	
Tank Capacity	6L	12L
Tank Size	250 x 200 x 150 mm	300 x 250 x 200 mm
Bath Opening	180 x 140 mm	235 x 160 mm
Bath Depth	150 mm	200 mm
Power Supply	AC 220v / 50 Hz	
Dimension	320 x 370 x 655 mm	320 x 370 x 765 mm
Packing Dimensions	530 x 450 x 800 mm	530 x 450 x 900 mm
Weight	44 kgs	50 kgs

STANDARD

ACCESSORIES:

- SS Lid
- Tube for connecting
- Instruction Manual