MODEL: EW-812



Elisa Microplate Washer



SALIENT FEATURES:

- 3.5 inch LCD display
- Easy to operate and save 100 wash programs
- Any line and hole can be easily cleaned, not necessary to clean the whole plate or strip
- Aspirating in 12 positions, residual volume <0.7µl
- Suitable for Flat, U and V-bottom micro-plates
- Detachable manifolds makes it easy to remove any particles in the manifolds
- Waste water sensor avoids overflow in the waste bottle
- Intelligent rinse procedure makes easy to maintain the device and reduces contamination between plates

SPECIFICATIONS:

ModelEW-812MakeGalaxyPlate ModelsFlat-, Round-, U-, V- plate (96-well and 48-wellWash Times8 and 12 wayWash Lines1 to 99 times adjustableResidual Volume1-12 lines selectableChannel<0.7μl/wellWash ModelPlates or StripsDispensing UniformityCV<1.5%Dispensing Volume50 to 950 μl, interval of 50 μlNo. of dispensing channels3 channel, can be extended to 5 channelsSoaking and shaking time0 to 999 (seconds/minutes/hours) adjustableAspiration Time0.1 to 9.9 seconds adjustable, interval 0.1 secondPipeline Wash Time0 to 240 seconds adjustableDistilled water wash interval0 to 20 platesPower SupplyAC 220V / 50 HzDimensions and Weight380 x 230 x 600 mm / 14 kgs		
Plate Models Flat-, Round-, U-, V- plate (96-well and 48-well Wash Times 8 and 12 way Wash Lines 1 to 99 times adjustable Residual Volume 1-12 lines selectable Channel Vash Model Plates or Strips Dispensing Uniformity CV<1.5% Dispensing Volume No. of dispensing channels Soaking and shaking time Aspiration Time Distilled water wash interval O to 20 plates Power Supply Plate (96-well and 48-well 8 and 12 way 8 and 12 way 1 to 99 times adjustable C0.7µl/well CV<1.5% Dispensing Color (950 µl) To 950 µl, interval of 50 µl O to 999 (seconds/minutes/hours) adjustable O to 999 (seconds adjustable, interval 0.1 second) O to 240 seconds adjustable Distilled water wash interval O to 20 plates Power Supply AC 220V / 50 Hz	Model	EW-812
Wash Times Residual Volume Channel Wash Model Dispensing Uniformity No. of dispensing channels Soaking and shaking time Aspiration Time Distilled water wash interval Pass Additional Sand 12 way 1 to 99 times adjustable 1-12 lines selectable <0.7µl/well Plates or Strips CV<1.5% Dispensing Uniformity CV<1.5% 3 to 950 µl, interval of 50 µl No. of dispensing channels 3 channel, can be extended to 5 channels 0 to 999 (seconds/minutes/hours) adjustable 0.1 to 9.9 seconds adjustable, interval 0.1 second Pipeline Wash Time 0 to 240 seconds adjustable Distilled water wash interval AC 220V / 50 Hz	Make	Galaxy
Wash Lines Residual Volume Channel Channel Vash Model Dispensing Uniformity Dispensing Volume No. of dispensing channels Soaking and shaking time Aspiration Time Distilled water wash interval Pates or Strips CV<1.5% To 950 µl, interval of 50 µl Ac 220V / 50 Hz To 99 times adjustable 1-12 lines selectable C0.7µl/well Plates or Strips CV<1.5% Dispensing Volume 50 to 950 µl, interval of 50 µl Oto 999 (seconds/minutes/hours) adjustable Ot 1 to 9.9 seconds adjustable, interval 0.1 second Pipeline Wash Time Oto 240 seconds adjustable Oto 20 plates Power Supply AC 220V / 50 Hz	Plate Models	Flat-, Round-, U-, V- plate (96-well and 48-well
Residual Volume Channel Channel Vash Model Dispensing Uniformity Dispensing Volume No. of dispensing channels Soaking and shaking time Aspiration Time Distilled water wash interval Power Supply 1-12 lines selectable 	Wash Times	8 and 12 way
Channel Vash Model Plates or Strips Dispensing Uniformity CV<1.5% Dispensing Volume So to 950 µl, interval of 50 µl No. of dispensing channels Soaking and shaking time Aspiration Time Oto 9.9 seconds adjustable, interval 0.1 second Pipeline Wash Time Oto 240 seconds adjustable Distilled water wash interval Oto 20 plates Power Supply AC 220V / 50 Hz	Wash Lines	1 to 99 times adjustable
Wash Model Plates or Strips CV < 1.5% Dispensing Uniformity 50 to 950 µl, interval of 50 µl No. of dispensing channels 3 channel, can be extended to 5 channels Soaking and shaking time 0 to 999 (seconds/minutes/hours) adjustable Aspiration Time 0.1 to 9.9 seconds adjustable, interval 0.1 second Pipeline Wash Time 0 to 240 seconds adjustable Distilled water wash interval 0 to 20 plates Power Supply AC 220V / 50 Hz	Residual Volume	1-12 lines selectable
Dispensing Uniformity CV < 1.5% Dispensing Volume 50 to 950 µl, interval of 50 µl No. of dispensing channels Soaking and shaking time O to 999 (seconds/minutes/hours) adjustable Aspiration Time O.1 to 9.9 seconds adjustable, interval 0.1 second Pipeline Wash Time O to 240 seconds adjustable Distilled water wash interval O to 20 plates Power Supply AC 220V / 50 Hz	Channel	<0.7µl/well
Dispensing Volume So to 950 μl, interval of 50 μl No. of dispensing channels Soaking and shaking time Aspiration Time Oto 9.9 seconds adjustable, interval 0.1 second Pipeline Wash Time Distilled water wash interval Power Supply AC 220V / 50 Hz	Wash Model	Plates or Strips
No. of dispensing channels Soaking and shaking time Aspiration Time Oto 9.9 seconds adjustable, interval 0.1 second Pipeline Wash Time Distilled water wash interval Power Supply AC 220V / 50 Hz	Dispensing Uniformity	CV<1.5%
Soaking and shaking time O to 999 (seconds/minutes/hours) adjustable Aspiration Time O.1 to 9.9 seconds adjustable, interval 0.1 second Pipeline Wash Time O to 240 seconds adjustable Distilled water wash interval O to 20 plates Power Supply AC 220V / 50 Hz	Dispensing Volume	50 to 950 μl, interval of 50 μl
Aspiration Time 0.1 to 9.9 seconds adjustable, interval 0.1 second Pipeline Wash Time 0 to 240 seconds adjustable Distilled water wash interval 0 to 20 plates Power Supply AC 220V / 50 Hz	No. of dispensing channels	3 channel, can be extended to 5 channels
Pipeline Wash Time 0 to 240 seconds adjustable Distilled water wash interval 0 to 20 plates Power Supply AC 220V / 50 Hz	Soaking and shaking time	0 to 999 (seconds/minutes/hours) adjustable
Distilled water wash interval O to 20 plates Power Supply AC 220V / 50 Hz	Aspiration Time	0.1 to 9.9 seconds adjustable, interval 0.1 second
Power Supply AC 220V / 50 Hz	Pipeline Wash Time	0 to 240 seconds adjustable
D' '	Distilled water wash interval	0 to 20 plates
Dimensions and Weight 380 x 230 x 600 mm / 14 kgs	Power Supply	AC 220V / 50 Hz
	Dimensions and Weight	380 x 230 x 600 mm / 14 kgs